

**TM - COPPER COMPRESSION TERMINAL (ONE HOLE / SHORT BARREL)**

TM-630

**Description**

**Purpose:** Termination of copper conductors.

**Characteristics:** High electrical conductivity and corrosion resistance. Pad with several hole diameter options and optimum electrical contact.

**Applications:** Electrical panels, circuit breaker connections, motors, machines, busbars, electrical distribution boards, among others.

**Material:** Electrolytic copper.

**Finish:** Tin plated.



**Datasheet**

**Conductors - Cross Section (mm<sup>2</sup>)** 630

**Dimensions (mm)**

|                       |       |
|-----------------------|-------|
| Diâmetro do Furo (mm) | 17,5  |
| Parafuso*             |       |
| Pol.                  | 5/8   |
| Métrico               | M16   |
| L                     | 61,2  |
| A                     | 125,0 |
| CB                    | 50,5  |
| AF                    | 32,5  |
| D                     | 51,0  |
| E                     | 6,3   |

**Current (A)** 1454

**Application Tool**

|                                    |   |
|------------------------------------|---|
| Alicate Mecânico                   |   |
| Modelo                             | - |
| Matriz (AT-60)                     | - |
| Alicate Hidráulico (AY-96 / CY-96) |   |
| Matriz Circunf.                    | - |
| Matriz Hexagonal                   | - |

**Package**

Qty / Emb

6

Peso Unit. (g)

416,20