

TM-L - COPPER COMPRESSION TERMINAL (ONE HOLE / LONG BARREL)

TM-150-L-17

Description

Purpose: Termination of copper conductors.

Characteristics: High electrical conductivity and corrosion resistance. Pad with several hole diameter options and optimum electrical contact.

Applications: Electrical panels, circuit breaker connections, motors, machines, busbars, electrical distribution boards, among others.

Material: Electrolytic copper.

Finish: Tin plated.



Datasheet

| | |
|--|-----|
| Conductors - Cross Section (mm²) | 150 |
|--|-----|

Dimensions (mm)

| | |
|-----------------------|------|
| Diâmetro do Furo (mm) | 17,5 |
| Parafuso* | |
| Pol. | 1/2 |
| Métrico | M12 |
| L | 30,0 |
| A | 79,5 |
| CB | 38,0 |
| AF | 13,0 |
| D | 29,5 |
| E | 3,6 |

| | |
|--------------------|-----|
| Current (A) | 577 |
|--------------------|-----|

Application Tool

| | |
|------------------------------------|-------|
| Alicate Mecânico | |
| Modelo | - |
| Matriz (AT-60) | - |
| Alicate Hidráulico (AY-96 / CY-96) | |
| Matriz Circunf. | IU-30 |
| Matriz Hexagonal | H-30 |

Package

Qtd / Emb

25

Peso Unit. (g)

65,60