

TF-2L - COPPER TERMINAL FOR FLEXIBLE CONDUCTORS (TWO HOLES / LONG BARREL)

TF-240-2L

Description

Purpose: Termination of copper conductors.

Characteristics: High electrical conductivity and corrosion resistance. Pad with several hole diameter options and optimum electrical contact. Expanded shape barrel for easy insertion of flexible conductors.

Applications: Electrical panels, circuit breaker connections, motors, machines, busbars, electrical distribution boards, among others.

Material: Electrolytic copper.

Finish: Tin Plated.



Datasheet

Conductors - Cross Section (mm²) 240

Dimensions (mm)

| | |
|-----------------------|-------|
| Diâmetro do Furo (mm) | 13,8 |
| Parafuso* | |
| Pol. | 1/2 |
| Métrico | M12 |
| L | 38,1 |
| A | 136,0 |
| CB | 42,0 |
| AF | 17,0 |
| D | 79,4 |
| E | 4,8 |

Current (A) 781

Application Tool

| | |
|------------------------------------|-------|
| Alicate Mecânico | |
| Modelo | - |
| Matriz (AT-60) | - |
| Alicate Hidráulico (AY-96 / CY-96) | |
| Matriz Circunf. | IU-34 |
| Matriz Hexagonal | H-34 |

Package

Qtd / Emb

20

Peso Unit. (g)

200,00